

Sipromac 600A


Get more out of your vacuum sealer with double chamber capabilities. You can maintain continuous production by having one chamber vacuuming while you're unloading and loading the other. Guaranteed, you will have sealed all your products in record time.

The pressure-controlled vacuum ensures evacuation and gas flushing processes are consistent and airtight every time.

The Sipromac 600A is made from stainless steel, features a Busch 100m³/h (5.0 hp) pump, (2) 26" seal bars per chamber, and a digital control panel that can store up to 20 different programs.

Specifications:

- Stainless Steel Construction
- Stainless steel lid
- Machine dimensions: 68" x 36" x 47"
- Chamber height: 8"
- Seal bar length: (4) 26.0"
- Distance between bars: 22.5"
- Element: Double seam band
- Vacuum Pump Busch 100m³ / 5.0 hp
- Electricity 208-220V/3Ph/60Hz
- Electricity: No cable and plug, requires electrician
- Microprocessor MC-40
- Vacuum Sensor - vacuum level controlled in percentage directly with Microprocessor
- Insert plates for sealing height adjustment
- Silencer - noise reducing of the vacuum aeration
- Wheels
- 1 Year Manufacturer's Warranty



Options:

- Electric cut-off
- Modified atmosphere packaging
- Air regulator
- Soft air function
- Stainless steel tilted insert
- 12" chamber height
- Bi-active seal
- Vacuum pump: Busch 200 m³/h
- Vacuum pump: Busch 300 m³/h
- Electricity: Various other voltages and/or single-phase power

