

## Sipromac 620A

Get more out of your vacuum sealer with double chamber capabilities. You can maintain continuous production by having one chamber vacuuming while you're unloading and loading the other. Guaranteed, you will have sealed all your products in record time.

The pressure-controlled vacuum ensures evacuation and gas flushing processes are consistent and airtight every time.

The Sipromac 620A is made from stainless steel, features a Busch 100m<sup>3</sup>/h (5.0 hp) pump, (2) 26" seal bars per chamber, and a digital control panel that can store up to 20 different programs.

### Specifications:

- Stainless Steel Construction
- Stainless steel lid
- Machine dimensions: 68" x 39.5" x 47"
- Chamber height: 8"
- Seal bar length: (4) 26.0"
- Distance between bars: 28.0"
- Element: Double seam band
- Vacuum Pump Busch 100m<sup>3</sup> / 5.0 hp
- Electricity 208-220V/3Ph/60Hz
- Microprocessor MC-40
- Vacuum Sensor - vacuum level controlled in percentage directly with Microprocessor
- Insert plates for sealing height adjustment
- Silencer - noise reducing of the vacuum aeration
- Wheels
- 1 Year Manufacturer's Warranty

### Options:

- Electric cut-off
- Modified atmosphere packaging
- Air regulator
- Soft air function
- Stainless steel tilted insert
- 12" chamber height
- Bi-active seal
- Vacuum pump: Busch 200 m<sup>3</sup>/h
- Vacuum pump: Busch 300 m<sup>3</sup>/h
- Electricity: Various other voltages and/or single-phase power

